



Product Data Sheet

7600D Temp Transmitter



The Model 7600D PC Programmable Temperature Transmitter is a highly accurate microprocessor based temperature transmitter.

The 7600D accepts a wide range of inputs – RTDs, Thermocouples, Resistance and Millivolt. The 7600D is loop-powered and provides a 4-20mA output signal.

Configure the 7600D with a PC and WeedComm Software.

The slim DIN rail design allows for many transmitters to be mounted in a small area.

- Low cost
- 0.08% accuracy
- Full input-output isolation
- Custom input/linearization capability
- Configurable via a PC or HART Communicator
- T/C Inputs: B, C, D, R, S, E, J, K, L, N, T, U
- RTD inputs: Pt100, Pt500, Pt1000, Ni100, Ni500, Ni1000
- mV Inputs: -10 to 75mV
- Ohm Inputs: 10 to 2000 ohms
- Outputs: 2-wire, 4-20mA or 20-4mA with optional HART signal superimposed

- Immediate shipment available!

Specifications

NAME	DESCRIPTION
Input Range:	Standard: Pt100, selectable range -328 to 1562F (-200 to 850C), minimum span 18F (10C) (Optional: various RTD and TC inputs accepted)
Output:	Standard 4-20mA (Optional: 20 to 4mA)
Zero & Span Adjustments:	Using WeedComm Software can be set anywhere within sensor range. Zero and Span are non interacting.
Failsafe:	Standard: upscale (Optional: downscale)
Response Time:	1 second
Damping:	User settable from 0 to 8 seconds
Isolation:	3750 VAC, input to output
Power Supply:	8 to 35VDC
Load Resistance:	$R_{Max} \text{ (ohms)} = (V_{Supply} - 8VDC) / .025A$
Accuracy:	For Pt100: .36F (0.2C) or 0.08% of span (whichever is greater)
Long Term Stability:	+/-0.05% of calibrated span per year
Cold Junction Compensation:	+/-1C (measured with Pt100 IEC 751, Class B)
Temperature Limit:	-40F to 185F (-40C to 85C)
EMI/RFI Effect:	Conforms to European Union Directives (CE Mark). Meet IEC 61326 amend 1, 1998 and NAMUR NE21.

NAME**DESCRIPTION**

Approvals:

Optional: Factory Mutual (FM), CSA and Intrinsically Safe (IS)

Accessories

USB Interface Programming Cable

0453-001-4005

WeedComm Programming Software

0453-001-4001

Documents

NAME

VIEW / DOWNLOAD

Instruction Manual

[View / Download](#)