

Round proximity sensor for aerospace

Overview

Our round proximity sensor is ideal for detecting the position of critical aircraft structures that are mechanically well controlled and have tighter geometric tolerances such as landing gear position. It has a single inductive core providing reliable variable inductive reluctance to sense changes with respect to its distance from a ferrous target. This proximity sensor will perform in applications with a gap range up to 0.100 inches.

Key features

- Round connector design for tighter geometric tolerance applications
- MIL-STD-38999 connector
- Hermetically sealed construction
- Stainless steel housing
- Corrosion resistant MIL-SPEC mounting hardware
- Standard or customer specified targets
- Round Sensor with MIL-STD-38999 connector 0.1013 lbs.
- ATA 32
- DO-160G environmental conditions and test procedures for airborne equipment
- MIL-STD-202G method 213B shock to 1,000 g
- 1,000,000 hour reliability
- AS9100 Quality Management System

Technical specification

Feature	Description
Type	Two-wire, passive proximity sensor, variable inductive reluctance
Electrical interface	MIL-DTL-38999 III circular connector, plug size 9, 3 position, cable (D38999/26FA98SN) or equivalent; sensor connector D38999/25 hermetic receptacle.
Connector pins	Pins A and C are connected, Pin B is not connected.
Principals	The inductance of the sensor changes with respect to its distance from a ferrous target. The sensor inductance increases in an exponential fashion as the target approaches the sensor face. Reference inductance values given at 1V @ 1000 Hz at room temperature (25°C).
Target material	17-4 Stainless steel per AMS 5604 heat treated H1050 condition
Inductance, target near	4.690 \pm 0.030 mH at 0.075" from a 1" diameter round target of thickness 0.1"
Inductance, target far	4.600 \pm 0.015 mH at 0.100" from a 1" diameter round target of thickness 0.1"
Side metal effect	The effect of (mild steel) side metal located behind the sensing face and with a 1mm gap (with respect to the threaded portion of the sensor) on the inductance of the sensor with a standard target with a gap of 1 mm shall is less than \pm 0.010mH.
Temperature effect	$\leq \pm$ 0.050mH throughout the operating temperature range (-55°C to +70°C) referenced from the initial inductance value in the far state with a target present at +20°C
Stability	$\leq \pm$ 0.5% of reading change over the qualified life of the sensor referenced from the initial measurement taken at ambient temperature with target in the near state

Technical specification

Feature	Description
AC resistance	9.24Ω ±10% at room temperature using an excitation frequency of 1,000 Hz ±0.1%
Dielectric strength	Dielectric strength (MIL-STD-202, Method 301) ≤ 1 mA dielectric strength of 1.07 kV RMS (1.5kV peak) applied for 1 minute between the input pins (A and C) and housing
Insulation resistance	Insulation resistance (MIL-STD-202, method 302) insulation resistance ≥ 20 MΩ with 1.5 kV DC applied for 2 minutes between the input pins (A and C) and the case
Bonding and grounding	The maximum resistance between any point on the sensor and the connector shell is 2.5mΩ. Bonding path to airframe is provided by mounting hardware.
Certification	Refer to RTCA DO-160G Environmental Procedures & Test Conditions for Airborne Equipment unless otherwise stated in this document
Ground survival low temperature	-55°C (Cat F2)
Short time low operating temperature	-55°C (Cat F2)
Low operating temperature	-55°C (Cat F2)
Ground survival high temperature	+85°C (Cat F2)
Short time high operating temperature	+70°C (Cat F2)
High operating temperature	+70°C (Cat F2)
Maximum operating altitude	50,000 ft (Cat D2)

Technical specification

Feature	Description
Decompression	50,000 ft
Overpressure	-15,000 ft
Temperature variation	-55°C to +70°C (Cat A
Humidity	Cat C
Operational shock	Cat B
Crash safety	Cat B
MIL-STD-202-213 shock (specified pulse)	3 shocks, 1,000 g's, in all 6 orthogonal directions ($\pm X$, $\pm Y$, and $\pm Z$, 18 shocks total) in accordance with MILSTD-202-213 (MIL-STD-202G Method 213B) Condition E.
High-level, short duration vibration	Cat H, Curve P
Robust vibration (sine)	Cat R, Curve W
Robust vibration (random)	Cat R, Curves E and E1
Explosion proofness	Cat H Zone II
Waterproofness	Cat S and R
Fluid susceptibility	Cat F applicable fluids: hydraulic fluids (phosphate ester-based (synthetic), Type IV, MIL-PRF-5606K hydraulic fluid, petroleum base), lubricating oils (mineral based, ester based), cleaning fluids (isopropanol alcohol, denatured alcohol, cleaning compound for aircraft surfaces), de-icing fluid (ethylene glycol propylene glycol, AEA Type 1, AEA Type 2, SAE Type 1, SAE Type 2, SAE Type 4, and runway deicer

Technical specification

Feature	Description
Sand and dust	Cat S
Fungus resistance	Cat F
Salt fog	Cat S
Magnetic effect	Cat A, test - as part of system
Power input	N/A - no power input
Voltage spike	N/A - no power input
Audio frequency conducted susceptibility	MIL-STD-461E test category CS101 note - N/A power lines only, Test – as part of system.
Induced signal susceptibility	MIL-STD-461E test category CS101, test – as part of system
Radio frequency susceptibility (radiated and conducted)	Cat YG, test – as part of system
MIL-STD-461E CS115 and CS116 (conducted susceptibility)	Test – as part of system.
Emission of radio frequency energy	Cat M except for subsection 21.4. MILSTD-461E test category RE103 in place of subsection 21.4. Cat H, test – As part of system.
Icing	Cat B, C
Static discharge	Cat A
Fire, flammability	Cat C
Storage temperature	+85°C

Technical specification

Feature	Description
Reliability	MTBF \geq 1,000,000 hours
Connector	Hermetic-passivated stainless steel
Housing material	304 stainless steel
Length	2.16"
Diameter	0.74" O.D.
Mounting threads	.625-24 UNEF-2A threads
Nut	MS21340-05, military standard plain hexagon nut, electrical thin (with lockwire holes), corrosion resisting steel
Washer	MS25081C6, military standard key washer, corrosion resisting steel
Installation torque	0.102 lbs (0.046 kg) - with 2 nuts and 1 washer 0.122 lbs (0.055 kg)
Weight	0.120 lbs (0.055 kg)
Packaging	Ultra Energy specified packaging is used for shipping and storage. A protective cap is installed over the sensor face prior to shipping. Remove cap prior to installation.
Accessories	Standard ferrous targets

FAQs

What are some aerospace applications for proximity sensors?

Proximity sensors are used on aircraft for sensing the position of critical structures including landing gears and doors, passenger and cargo doors, slats and flaps and thrust reversers.

What target material is suitable for aerospace proximity sensors?

Sensor can detect ferrous metals only. Aluminum will cause deactuation and can therefore serve as an anti-target.

Will Ultra Energy perform a 'test - as part of system'?

Electrical interface circuitry typically resides in landing gear control unit or proximity sensor electronics unit or proximity sensor module. Note that all tests designated as 'test - as part of system' will only be performed at customers' request.



About Ultra Energy

Organizations working with nuclear and industrial technologies must deliver reliable production at the same time as safeguarding people, the environment and infrastructure. We develop and manufacture measurement and control solutions that give our customers complete, long-term control over systems operating in harsh environments, helping them operate safely and increasing the value derived from their investments over their total lifespan.

Part of Ultra Group, a global electronics company, Ultra Energy has worked with nuclear and industrial customers for over 60 years. We support customers across the world from facilities located in the US and UK. Our solutions are embedded in strategic national infrastructure and our people are active partners in customer programs that are focused on delivering advanced future nuclear and industrial capabilities.

United States of America

707 Jeffrey Way
Round Rock
Texas 78665-2408
USA

Tel: +1 512-434-2800

United Kingdom

Innovation House
Lancaster Road
Ferndown Industrial Estate
Wimborne
Dorset BH21 7SQ
UK

Tel: +44 (0) 1202 850 450

For more information

Web: ultra.energy

Email: sales@ultra.energy