



# 733 duct temperature sensor



### Overview

Accurately senses temperature at a point inside a duct or plenum.

Low cost rugged design.

High quality sensor constructed of 316 stainless steel.

For ease of installation, unit mounts with only two screws, and is supplied with a gasket to prevent air leakage from duct.

Sensor is easily removable without dismounting the unit.

Ideal for remote sensing when used in conjunction with optional temperature transmitter





## Technical specification

Feature	Description
Element type	Standard platinum, 100 ohms @ 0C (32F), .00385, TCR, with optional Pt1000 and 10K thermistor
Accuracy	Standard DIN-B
Termination housing	Standard galvanized steel utility box, with optional NEMA4 steel box available
Sensor sheath length	Standard 2 to 18 inches
Maximum operating temperature	65°C (150°F)
Sensor lead wire	Three 24 AWG Teflon insulated
Insulation resistance	Greater than 100 Megohms @ 100VDC @ 21C (70F)
Accessory	4500H transmitter (0502-157-0003)



## **About Ultra Energy**

Organizations working with nuclear and industrial technologies must deliver reliable production at the same time as safeguarding people, the environment and infrastructure. We develop and manufacture measurement and control solutions that give our customers complete, long-term control over systems operating in harsh environments, helping them operate safely and increasing the value derived from their investments over their total lifespan.

Part of Ultra Group, a global electronics company, Ultra Energy has worked with nuclear and industrial customers for over 60 years. We support customers across the world from facilities located in the US and UK. Our solutions are embedded in strategic national infrastructure and our people are active partners in customer programs that are focused on delivering advanced future nuclear and industrial capabilities.

### **United States of America**

707 Jeffrey Way Round Rock Texas 78665-2408 USA

Tel: +1 512-434-2800

## **United Kingdom**

Innovation House Lancaster Road Ferndown Industrial Estate Wimborne Dorset BH21 7SQ UK

Tel: +44 (0) 1202 850 450

### For more information

Web: <u>ultra.energy</u>

Email: <a href="mailto:sales@ultra.energy">sales@ultra.energy</a>

