

2104-61 industrial ethernet ring switch



Key features

- Fault-tolerant self-Healing ring (SHR) with 30ms plus 5ms per hop recovery time
- Pre-configured from factory for SHR operation
- 10/100 Base-T(X) (RJ45), 100 Base-FX (SC or ST optical fiber connectors, Multi/Single Mode)
- Supports IEEE 802.3, 802.3u, 802.3z and 802.1p

Overview

The EOTec 2104 is a rugged, high performance industrial Ethernet ring switch that is designed to fill the gap between unmanaged and managed Ethernet switches. It provides all the benefits of redundant ring topology operation, but at a significantly lower cost than managed switches. The 2104 features the simplicity of installation and operation of an unmanaged switch, while retaining many of the capabilities of a managed switch. It is pre-configured for ring topology and no setup or configuration is required. It doesn't require master switch selection or an IP address to operate in a redundant ring topology. Its ultra fast link loss recovery time ensures high reliability with minimal downtime.

Technical specification

Further features

- Intelligent store and forward, non-blocking
- Full/Half Duplex, MDI/MDIX auto crossover, auto negotiate, auto polarity
- Expandable up to 8 ports
- Long-haul transmit distances of 2, 15, 40 and 60km
- Real-time traffic prioritization
- 45mm wide, DIN rail mounted
- Universal redundant power supply available
- Low power consumption (8W)
- Power and switch status LED indicator
- Global ring status alarm LED indicator
- Expandable backplane
- Remote status monitoring using Modbus over Ethernet (UDP)
- Local and global relay alarm contacts
- Port status ACT and LINK LEDs combined into one LED per port
- Backplane port activity status LED indicator
- Two SC or ST 100base-FX (multi-mode and single mode) fiber optic ports
- Pre-configured for redundant self-healing ring operation

Feature	Description
Fiber type	Single-mode
Connector type	SC
Port configuration	4-port (2 RJ45 and 2 fiber)
Power requirements	15-40 Vdc via screw terminals
Maximum transmission distance	40km
Operating temperature range	-40 to +85°C
Approvals	Class 1, Division 2, Groups A, B, C, D - CE marked
Acessories	<ul style="list-style-type: none">• Optional power supply modules: 2A06, 2A16• Expansion modules for additional ports: 2E54, 2E56, 2E58, 2E60, 2E62, 2E52
User manual	Shipped with product or available on request



About Ultra Energy

Organizations working with nuclear and industrial technologies must deliver reliable production at the same time as safeguarding people, the environment and infrastructure. We develop and manufacture measurement and control solutions that give our customers complete, long-term control over systems operating in harsh environments, helping them operate safely and increasing the value derived from their investments over their total lifespan.

Part of Curtiss-Wright, Ultra Energy has worked with nuclear and industrial customers for over 60 years. We support customers across the world from facilities located in the US and UK. Our solutions are embedded in strategic national infrastructure and our people are active partners in customer programs that are focused on delivering advanced future nuclear and industrial capabilities.

United States of America

707 Jeffrey Way
Round Rock
Texas 78665-2408
USA

Tel: +1 512-434-2800

United Kingdom

Innovation House
Lancaster Road
Ferndown Industrial Estate
Wimborne
Dorset BH21 7SQ
UK

Tel: +44 (0) 1202 850 450

For more information

Web: ultra.energy
Email: sales@ultra.energy