

753 room air temperature sensor



Overview

Attractively styled wall mounted housing designed for even air flow around the sensor for optimal time response.

Unique housing design reduces the effects of self-heating created by the transmitter circuitry.

Ideal for remote sensing when used in conjunction with optional temperature transmitter

Technical specification

Feature	Description
Element type	Standard platinum, 100 ohms @ 0C (32F), .00385, TCR, with optional Pt1000 and 10K thermistor
Accuracy	Standard DIN-B
Termination housing	Standard galvanized steel utility box, with optional NEMA4 steel box available
Sensor sheath length	Standard 2 to 18 inches
Maximum operating temperature	65°C (150°F)
Sensor lead wire	Three 24 AWG Teflon insulated
Insulation resistance	Greater than 100 Megohms @ 100VDC @ 21C (70F)
Accessory	4500H transmitter (0502-157-0003)

About Ultra Energy

Organizations working with nuclear and industrial technologies must deliver reliable production at the same time as safeguarding people, the environment and infrastructure. We develop and manufacture measurement and control solutions that give our customers complete, long-term control over systems operating in harsh environments, helping them operate safely and increasing the value derived from their investments over their total lifespan.

Part of Curtiss-Wright, Ultra Energy has worked with nuclear and industrial customers for over 60 years. We support customers across the world from facilities located in the US and UK. Our solutions are embedded in strategic national infrastructure and our people are active partners in customer programs that are focused on delivering advanced future nuclear and industrial capabilities.

United States of America

707 Jeffrey Way
Round Rock
Texas 78665-2408
USA

Tel: +1 512-434-2800

United Kingdom

Innovation House
Lancaster Road
Ferndown Industrial Estate
Wimborne
Dorset BH21 7SQ
UK

Tel: +44 (0) 1202 850 450

For more information

Web: ultra.energy

Email: sales@ultra.energy